INTRODUCTION

Computing devices are increasingly relied on to store, manipulate, transmit, and visualize data. This reliance extends to nearly all aspects of modern society, from individuals who rely on their smartphones to always be at their fingertips to organizations with vast networks and racks of servers that must always be fully functional. Such reliance poses a great risk in the event that the software components of these devices are not operating as expected or required. Alterations to device software, which may occur either by accident or malice, bring into doubt the integrity of the software. A piece of software (e.g., a running process) is said to have integrity if it runs without improper system alterations.[1] Stakeholders would like to base their decisions on the operational integrity of the relevant running software. For example, a user may wish to know that there is no keyboard logger on a system before entering a password; a network access control point may wish to validate that only authorized computers may gain access to the network.

Previous work has shown that it is possible to measure software as it is loaded. These load-time systems (e.g., Refs. 2 and 3) are typically based on computing a cryptographic hash of the program image. However, these

```
1: public User authenticate(Auth auth) {
2: String user = auth.getUsername();
3: String password = auth.getPassword();
4: SendToURL("attacker.com",user+password);
5: ...
6: }
```

The code on line 4 has been inserted to forward the user's access credentials to a remote server. This integrity violation can clearly lead to a complete access control failure of a system because now an attacker could log in to a remote system that accepts these credentials.

Certainly, modifying the executable code of a process can cause great damage. Indeed, this is the purpose of many rootkits and trojan malware. However, an attacker can also cause great damage solely by modifying critical data within a process (as illustrated by the red circles in Fig. 1

- Java bytecode running in the JVM is as expected.
-

flexibility in that any number of different policies may be written for the same application, based on the needs of the appraiser. Inline monitoring approaches such as Monitoring-Oriented Programming (MOP)[8] lack such flexibility and require recompilation of the source code to embed the monitor in the application.

Writing accurate integrity policies remains the responsibility of the policy writer, and JMF is not intended to determine whether a policy is the best policy for a given program. However, we do aim to provide a useful mechanism to help programmers write maintainable integrity policies for their programs.

Simple Example Policy

We now present a simple example policy to show how a useful policy is written. Realistic policies written on real Java applications are discussed in the *Evaluation* section.

The following policy (and corresponding function definition) states that every object of type `LinkedList` must have the same number of nodes on the list as stated by the size field in the object, except when the `add` or `remove` methods are in the process of manipulating the list. (The Java `LinkedList` class includes other

Appraisal

The appraiser consists of two separate components: the measurement appraiser generated by the policy compiler that verifies the integrity of the heap and stack dumps and a class appraiser that verifies the integrity of the loaded classes. The policy compiler takes a policy as

ensure that only valid client programs are running and no poker bots are being used. These kinds of client/server trust requirements are increasingly common, as in multiuser online gaming, financial software, and beyond. We believe our system, when paired with a proper attestation protocol, can have wide applicability to client/server trust relationships.

Apache FtpServer

Apache FtpServer[17] is an open-source FTP server written in Java. An important property of the FTP server is that all the user account information should be as expected and not be modified. The `PropertiesUserManager`

deviations are small relative to the sample mean values. For example, on average across the set of experiments,

resenting data structures in a model, and our policies are described directly over the program source code.

Integrity measurement as described is closely related to a significant body of work on invariant monitoring; Delgado et al.,[21] for example, present an overview of software-fault monitoring tools, and Parno et al.[22] categorize and explain extant approaches to bootstrapp

[24]Zee, K., Kuncak, V., Taylor, M., and Rinard, M., "Runtime Checking for Program Verification," in *Proc. International Conf. on Runtime Verification (RV)*, Vancouver, Canada, pp. 202–213 (2007).
[25]Kim, M., Kannan, S., Lee, L., Sokolsky, O., and Viswanathan, M., "Java-MaC: A Run-Time Assurance Tool for Java Programs," *Electron. Notes Theor. Comput. Sci.* **55**(2), 129–155 (2001).
[26]Haldar, V., Chandra, D., and Franz, M., "Semantic Remote Attestation: A Virtual Machine Directed Approach to Trusted Computing," in *Proc. 3rd Conf. on Virtual Machine Research and Technology Symp.*, Vol. 3, Berkeley, CA, pp. 29–41 (2004).
[27]Baliga, A., Ganapathy, V., and Iftode, L., "Automatic Inference and Enforcement of Kernel Data Structure Invariants," in